

SKG4 GAS FIRED HUMIDIFIER

Output and Consumption - 60Hz

Model	No. of Modules	Steam Capacity (lb/hr) [kg/hr]	Input Capacity (btu/hr)[kW]	Current at 120Vac (A)	Current at 208Vac (A)	Current at 240Vac (A)	No. of Outlets	Multi-Steam header diam. in [mm]
SKG4-N1101 N/P	1	110 [50]	165,000 [49]	6.0	3.5	3.0	1	3" [76]
SKG4-N1551 N/P	1	155 [70]	215,000 [63]	6.0	3.5	3.0	1	3" [76]
SKG4-N1801 N/P	1	180 [80]	240,000 [70]	6.0	3.5	3.0	1	3" [76]
SKG4-N2101 N/P	1	210 [95]	249,000 [73]	6.0	3.5	3.0	1	3" [76]
SKG4-N2652 N/P	2	265 [120]	380,000 [112]	9.0	5.2	4.5	2	4" [100]
SKG4-N3102 N/P	2	310 [140]	430,000 [126]	9.0	5.2	4.5	2	4" [100]
SKG4-N3502 N/P	2	350 [160]	464,000 [136]	9.0	5.2	4.5	2	4" [100]
SKG4-N4052 N/P	2	405 [185]	498,000 [146]	9.0	5.2	4.5	2	4" [100]
SKG4-N5053 N/P	3	505 [230]	704,000 [206]	12.0	7.0	6.0	3	5" [125]
SKG4-N5603 N/P	3	560 [255]	713,000 [209]	12.0	7.0	6.0	3	5" [125]
SKG4-N6103 N/P	3	610 [275]	746,000 [219]	12.0	7.0	6.0	3	5" [125]
SKG4-N7104 N/P	4	710 [320]	953,000 [279]	15.0	8.7	7.5	4	(2x) 4" [100]
SKG4-N7654 N/P	4	765 [345]	962,000 [282]	15.0	8.7	7.5	4	(2x) 4" [100]
SKG4-N8104 N/P	4	810 [370]	996,000 [292]	15.0	8.7	7.5	4	(2x) 4" [100]



Output and Consumption - 50Hz

Model	No. of Modules	Steam Capacity (kg/hr)	Input Capacity (kw)	Current at 230V (Amp)	Multi-Steam header diameter (mm)
SKG4-E0501 N/P	1	50	49	3.5	76
SKG4-E0701 N/P	1	70	63	3.5	76
SKG4-E0801 N/P	1	80	70	3.5	76
SKG4-E1001 N/P	1	100	73	3.5	76
SKG4-E1202 N/P	2	120	112	4.5	100
SKG4-E1502 N/P	2	150	126	4.5	100
SKG4-E1702 N/P	2	170	136	4.5	100
SKG4-E2002 N/P	2	200	146	4.5	100
SKG4-E2503 N/P	3	250	206	6.0	125
SKG4-E2703 N/P	3	270	209	6.0	125
SKG4-E3003 N/P	3	300	219	6.0	125
SKG4-E3504 N/P	4	350	279	7.5	2x 100
SKG4-E3704 N/P	4	370	282	7.5	2x 100
SKG4-E4004 N/P	4	400	292	7.5	2x 100